


FS273M

A Cost-performance Solution for Robust Metal Production

► www.farsoon-gl.com



SIMPLY METAL PRODUCTION

With an industrial-sized 275×275×355mm build envelope as well as an expanded powder feeding cylinder size, FS273M offers streamlined metal production of larger volume parts with a wide range of industrial metal powder materials.

COST-PERFORMANCE

The FS273M metal laser sintering system is a high value proposition industrial production tool. Advanced digital optics system, robust controls, and truly open parameters gives users a much wider range of process capabilities. The FS273M is able to achieve highly detailed, functional parts while maintaining a price competitive advantage. Compact machine design enables denser, flexible factory layout for maximum throughput yield per floor area at an economical additive production cost.

OPERATION EASE & GOOD SERVICEABILITY

The FS273M features an integrated permanent filtration module which allows uninterrupted process for enhanced operational ease and safety. Other convenient features including pre-heated base plate, robust recoater operations, removable overflow containers, and a powder supply sufficient for a full build ensures ease of operation and good serviceability.

FARSOON FS273M

TECHNICAL DATA		FS273M	FS273M-2
External Dimension (L×W×H)	2930×1660×2390mm (115.4×65.4×94.1 in)		
Build Cylinder Size (L×W×H) (Height incl. build plate)	275×275×355 mm (10.8×10.8×14.0 in) (φ165×145 mm small circular cylinder optional)		
Effective Build Size ¹ (L×W×H) (Height incl. build plate)	271×271×355 mm (10.7×10.7×14.0 in) (φ161×145 mm small circular cylinder optional)		
Net Weight	Approx. 3300 kg (7275.3 lb)		
Layer Thickness	0.02~0.1 mm (0.0008-0.0039 in)		
Scanning Speed ²	Max. 10 m/s (32.8 ft/s)		
Laser Type	Single Laser, 1×500W, Optional 1×1000W	Dual Lasers, 2×500W, Optional 2×1000W	
Scanner	F theta lenses		
Inert Gas Protection	Argon/Nitrogen		
Average Inert Gas Consumption in Process	3-5 L / min		
Operating System	64 bit Windows 10		
Comprehensive Software	BuildStar, MakeStar®		
Key Software Features	Open machine key parameters, real-time build parameter modification, three-dimensional visualization, diagnostic function, support-add function		
Data File Format	STL		
Power Supply	EUR/China: 400V±10%, 3~N/PE, 50Hz, 30A US: transformer sold with machine		
Operating Ambient Temperature	22-28°C (71.6-82.4°F)		
Materials ³	Ti6Al4V, TA15, AISi10Mg, 316L, 420DS, H13, IN718, CuCrZr, Hastelloy X, CoCrMo, Maraging Steel Grade 300, 17-4PH*, AlMgSc*, AISi7Mg*, Pure Copper*, W*, Ta*, more materials to come		

1 The functional build volume depends on the parts/materials.
2 For different industries and customer needs, this data may vary.
3 The materials marked with * are in the build process development.

Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, Buildstar®, Makestar® are registered trademarks of Farsoon Technologies. Last Change: 2025-10

