

FS3401GB-F

Developed for FLIGHT® Technology

Advanced PA12-based Glass Bead Reinforced
Polymer Material

Key Features:

- > Excellent mechanical strength and rigidity
- > Extraordinary dimensional stability
- > Good thermal/abrasive resistance

Example Applications:

- > Perfect for functional end-use parts production
- > Ideal for industrial applications such as automotive engine system, electrical tools.

[Technical Data]

General Properties

Bulk Density	0.65 g/cm ³
Part Density	1.30 g/cm ³
Color	Black

Thermal Properties

Melting Point (10°C/min) ISO 11357-1:2020	185.5 °C
Heat Deflection Temp(HDT) @1.8 MPa ISO 78-1:2020	62 °C
Heat Deflection Temp(HDT) @0.45 MPa ISO 78-1:2020	157 °C

Mechanical Properties

Tensile Strength ISO 527-1:2019	47 MPa
Tensile Modulus ISO 527-1:2019	2810 MPa
Elongation at Break ISO 527-1:2018	8.7%
Flexural Strength ISO 178:2019	73 MPa
Flexural Modulus ISO 178:2019	2550 MPa
Izod Impact Strength (notched) ISO 180:2019	9.5 KJ/m ²
Izod Impact Strength (unnotched) ISO 180:2019	23 KJ/m ²

Disclaimer: Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, Buildstar®, Makestar® are registered trademarks of Farsoon Technologies. Last Change: 2022-01-29



Engine Intake Manifold
System: FLIGHT® HT252P



HVAC Defrost Duct
System: FLIGHT® HT252P

www.farsoon.com