

FLIGHT® HT1001P

×4 Laser | ×3 Power | ×3 Volume¹ | Ultimate System for Productivity

► www.farsoon-gl.com



QUAD-FIBER LASER FOR MAXIMUM PRODUCTIVITY

The innovative application of high-speed Flight® Technology on HT1001P CAMS platform boosts industry-leading productivity for large-sized parts. Featuring expanded build cylinder measuring 1000mm×500mm×450mm and powerful quad 300-watt fiber lasers, the Flight® HT1001P creates four ultra-fine laser spots with fast scanning speed of up to 20m/s (66ft/s) for each; the continuous batch production capability significantly improves machine uptime and offers maximum throughput yield per floor area within the same time frame.

QUALITY ENGINEERING PARTS

The Flight® HT1001P is capable of achieving chamber temperatures of up to 220 °C to process high-temperature engineering materials such as PA6 for direct-use end parts. With patented multi-zone heater & intelligent temperature control system, the Flight® HT1001P can achieve a uniform thermal distribution throughout the platform ensuring the consistent mechanical properties and surface quality of the build parts.

POWDER MANAGEMENT

Designed for industrial-scale manufacturing, the Flight® HT1001P system is featured with a comprehensive, closed-loop powder handling system with increased level automation and minimal operator interaction with the powder. Highly efficient top-feeding powder delivery, robust roller re-coating system and fully enclosed de-powdering station enables streamlined material workflow with improved productivity, safety and operation ease.

OPEN & MODULAR

The Flight® HT1001P like all Farsoon systems is fully open. This means Farsoon system is an open material model. Besides a list of standard material config files ready for serial production, users have full access to a wide range of key parameters for tuning customized processing parameters from third party engineering materials. In addition, the Flight® HT1001P's modular design allows for the easy addition of future stations for pre and post processing as well as integration into existing production lines.




FARSOON FLIGHT® HT1001P

TECHNICAL DATA		FLIGHT® HT1001P-4
External Dimensions (L×W×H)	5820×2375×2185 (Full Module) (229.1×93.5×86.0 in) , 2960×2375×2185 mm (Build Station only) (116.5×93.5×86.0 in)	
Build Cylinder Size ² (L×W×H)	1000×500×450 mm (39.4×19.7×17.7 in)	
Net Weight	Approx. 5000 KG (11023.1 lb) (Full Module) / 3500KG (7716.2 lb) (Build Station only)	
Laser Type	Fiber Laser, 4×300W	
Scanner	High-precision three-axis galvo system	
Layer Thickness	0.06~0.3 mm (0.0024-0.0118 in)	
Scanning Speed	Max. 20 m/s (66 ft/s)	
Max. Chamber Temperature	220°C (428°F)	
Thermal Field Control	Multi-zone heater & Intelligent temperature control systems	
Temperature Regulation	Continuous real-time build surface temperature monitoring & optimization	
Operating System	64 bit Windows 10	
Comprehensive Software	BuildStar, MakeStar®	
Data File Format	STL	
Key Software Features	Open machine key parameters, real-time build parameter modification, three-dimensional visualization, diagnostic functions	
Inert Gas Protection	Nitrogen	
Power Supply	EUR/China: 400V±10%, 3~N/PE, 50/60Hz, 50A US: transformer sold with machine	
Operating Ambient Temperature	22-28°C (71.6-82.4°F)	
Materials	FS3200PA-F, FS3201PA-F, FS3401GB-F, FS6140GF-F, WANFAB-PU95AB, Ultrasint® TPU 88A black, LUVOSINT® TPU X92A-1064 WT, Ultrasint® PA11 Black, more materials to come	

1 Numbers of laser, laser power and build volume comparable to Farsoon SS403P system.
2 The functional build volume depends on the parts/materials.

Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, Buildstar®, Makestar® are registered trademarks of Farsoon Technologies. Last Change: 2025-10



Flow Channel Plate
MATERIAL: FS3200PA-F
SYSTEM: Flight® HT1001P-4
SIZE: 930×219×262 mm (36.6×8.6×10.3 in)
PRINT TIME: 14h/2pcs

www.farsoon-gl.com